




# **TS PERFORMANCE**

## **WE ARE DIESEL**



### ***MP-8***

### ***1110308***

### ***2014-2015 Ram 1500 3.0L***

### ***Installation Manual***

**Thank you for buying the MP-8 for the 2014-2015 Ram 3.0L. Here you will learn how to install this MP-8 into your truck, and we guarantee that you will be satisfied with our product. Before you get started check to make sure that you have everything below in the contents that came in the box.**

#### ***Contents:***

**MP-8 Module  
(4) Zip Ties**

**Harness (TSP-15DO)  
Switch (TSP100)**

- **HP increase of up to 50hp**
- **Decrease Fuel Consumption**
- **When removed leaves no trace of modification or foot prints**

**Continued**

## **Installation of the TS Performance Power Play Mp-8 2014-2015 Ram 1500 3.0L**

Read all instructions and fully understand them before installing your TS Performance MP-8 module. Disconnect the battery terminals and remove keys from ignition before installation.

### **1. Disconnect the positive terminals on both batteries.**

Failure to do this will cause a Check Engine Light and it will have to be cleared with a code reader. (Any time the module is installed or removed, the batteries must be disconnected.)

- 2. Remove the plastic engine cover and set to the side. Both connections you will be accessing are located under it.**



- 3. Remove the air filter tube and the foam padding under the engine cover.**



## Continued

4. Once the foam padding is removed this is what you will see. The MAP sensor is located directly in front of the turbo and its location is indicated by the yellow circle in our picture.

Disconnect the wire harness going to this sensor. Connect the (4) pin connector in our harness to both the MAP sensor and to the harness going to it.

5. The Fuel Pressure Sensor location is indicated in this picture by the red circle. It will be in the end of the fuel rail on the passenger's side of the engine. Disconnect the wire harness going into it. Connect the (3) pin connector on our harness to both the fuel pressure sensor and the factory wire harness.

6. At this point the only connectors that will be open are the connector going to the MP8 module and the connector that goes to the switch.
7. Re install the foam padding, the air filter tubing, and the plastic engine cover.
8. Now you will want to mount the MP8 where it is secure and away from hot or moving parts. We usually zip tie it to a wire harness on the firewall.
9. Route the harness to the MP8 and connect it to the MP8 case.
10. Route the switch into the cab where it can be adjusted while driving and plug it into the short three pin wire harness coming off the MP8. The power can be increased by turning the knob clockwise. With the knob turned all the way counter clockwise the truck should run as stock. When turned all the way clockwise you will see an increase of 50HP and your best fuel economy.



## **Continued**



TS Performance  
851 Lovers Ln  
Bowling Green, KY 42103  
270-746-9999  
[www.tsperformance.com](http://www.tsperformance.com)

### **READ CAREFULLY BEFORE INSTALLING ANY TS PERFORMANCE PRODUCT**

**REMEMBER THIS IS A HIGH PERFORMANCE PRODUCT. USE AT YOUR OWN RISK. FOR OFF ROAD USE ONLY.**

**Do not use this product until you have carefully read the following agreement.** This agreement sets forth the terms and conditions for the use of the TS Performance product. The installation of this product indicates that the buyer has read and fully understands this agreement and accepts its terms and conditions.

#### **DISCLAIMER OF LIABILITY**

TS Performance, its distributors or dealers shall in no way be responsible for the product's proper use and service. The buyer of this system hereby waives all liability claims. The buyer acknowledges that he is not relying on the seller's skill or judgment to select or furnish goods suitable for any particular purpose and that there are no liabilities which extend beyond the description on the face hereof, and the buyer hereby waives all remedies or liabilities, expressed or implied arising by law or otherwise, (including without obligations of the seller with respect to fitness, merchantability and consequential damages) or whether or not occasioned by the seller's negligence.

The seller disclaims any warranty and expressly disclaims any liability for personal injury or damages. The buyer acknowledges and agrees that the disclaimer of any liability for personal injury is a material term for this agreement and the buyer agrees to indemnify the seller and to hold the seller harmless from any claim related to the item of the equipment purchased. Under no circumstances will the seller be liable for any damages or expenses by reason of use or sales of any such equipment.

The seller assumes no liability regarding the improper installation or misapplication of its products. It is the installer's responsibility to check for proper installation and if in doubt the manufacturer is to be contacted.

#### **LIMITED LIFETIME WARRANTY**

##### **STATEMENT POLICY**

- The warranty policy is the best warranty within the high performance diesel industry.
- All **TS Performance** products have been inspected, tested and trial in the factory laboratories and on the field.
- Nothing in this Statement of Policy shall alter or enlarge the terms of warranties, obligation or liabilities of these products.
- **TS Performance** is not responsible or liable for any products damaged or destroyed due to improper installation.

##### **TERMS OF WARRANTY**

- The defective product must be freight prepaid and returned to **TS Performance** for further investigation, otherwise this warranty shall be deemed null and voided and of no effect.
- This warranty is void on any products that show evidence of misapplication, negligence, and improper installation, and abuse, lack of proper maintenance or alternation from its original design.
- In no event will **TS Performance** be liable for any consequential or incidental damages for breach of any express or implied warranty on the product.
- This warranty is not transferable or assignable.
- **TS Performance** is not responsible or liable for any products damaged or destroyed due to improper installation
- **IN THE EVENT THAT THE BUYER DOES NOT AGREE WITH THIS AGREEMENT: THE BUYER MAY PROMPTLY RETURN THIS PRODUCT IN A NEW ANDN UNUSED CONDITION WITH A DATED PROOF OF PURCHASE TO THE PLACE OF PURCHASE WITHIN TEN (10) DAYS FROM DATE OF PURCHASE FOR A FULL REFUND.**

***Continued***

**TS PERFORMANCE**  
**Products and Other Info found on the**  
**[WWW.TSPERFORMANCE.COM](http://WWW.TSPERFORMANCE.COM)**

**FOR TECHNICAL SUPPORT**  
**(270) 746-9999**



**WE ARE DIESEL**