



TS PERFORMANCE



EcoPro 1310403 2015 + Ford 2.3L EcoBoost Installation Manual

Thank you for buying the EcoPro for the 2015+ Ford 2.3L EcoPro. Here you will learn how to install this EcoPro into your truck, and we guarantee that you will be satisfied with our product. Before you get started check to make sure that you have everything below in the contents that came in the box.

Contents:

**EcoPro Module
Zip Ties (4)**

**Harness
Switch (TSP100)**



- **HP increase of up to 50+**
- **Decrease Fuel Consumption**
- **When removed leaves no trace of modification or foot prints**

Continued

Installation of the TS Performance EcoPro 2015+ Ford 2.3L EcoBoost

Read all instructions and fully understand them before installing your TS Performance EcoPro module. Disconnect the battery terminals and remove keys from ignition before installation.
Place Di-Electric Grease onto every electrical connection.

1. The first step in installing your new TS Performance EcoPro module is locate the connections we will be going into. The first is the MAP sensor. On the 2.3L engine it is located on the driver's side of the engine right beside the engine cover. It is identified in the first and second pictures by the red circle
2. Now remove the factory connector from the MAP sensor and connect the matching connectors on our harness to the MAP sensor and the factory harness you just removed.
3. Now you will need to route the end of our harness down toward the driver's side front corner.
4. To access the TIP sensor you will need to remove the lower cover. To do this you will have two options of your choice to gain access to this sensor. The first is to remove the driver's side wheel and




Continued

lower the inner fender on the front side of the wheel well. The second option is to raise the vehicle up on jackstands or a lift and remove the lower engine compartment cover. We opted to remove the engine compartment cover to allow for the best pictures we could get. On our 2016 Mustang we removed (16) 7mm bolts and (6) plastic push pins to loosen the cover. It will then slide back and come completely out of the way.



5. Looking in from the driver's side of the car you can now see the TIP sensor on the side of the innercooler just above where the cooler pipe comes out. The sensor and connector are shown in the picture to the right.



6. Now disconnect the harness going to this sensor and connect our EcoPro harness to the sensor and the factory harness.
7. Now that this is connected you can replace the lower engine compartment cover.
8. The next step is to route the end of the harness that connects to our EcoPro module over toward the driver's side fender and connect it to the Ecoro module. You will need an 8mm socket to connect the harness to the module.
9. Now go back and zip tie the EcoPro harness to existing wires to keep it from getting against extreme heat or moving parts.

Continued

10. Once you have the module mounted you are ready to run the switch through the firewall. We usually route the three pin connector through the existing grommet in the firewall and connect it to the EcoPro harness.
11. The knob can now either be mounted on the dash or zip tied under the dash out of your way. Just make sure the harness will not be in the way of accessing the control pedals or rubbing the steering linkage.
12. The switch can be adjusted while driving to control the maximum power gains allowed. The adjustment will go from stock power to the 50+Hp setting and can be set anywhere in between.



Continued



TS Performance

851 Lovers Ln
Bowling Green, KY 42103
270-746-9999
www.tsperformance.com

READ CAREFULLY BEFORE INSTALLING ANY TS PERFORMANCE PRODUCT

REMEMBER THIS IS A HIGH PERFORMANCE PRODUCT. USE AT YOUR OWN RISK. FOR OFF ROAD USE ONLY.

Do not use this product until you have carefully read the following agreement. This agreement sets forth the terms and conditions for the use of the TS Performance product. The installation of this product indicates that the buyer has read and fully understands this agreement and accepts its terms and conditions.

DISCLAIMER OF LIABILITY

TS Performance, its distributors or dealers shall in no way be responsible for the product's proper use and service. The buyer of this system hereby waives all liability claims. The buyer acknowledges that he is not relying on the seller's skill or judgment to select or furnish goods suitable for any particular purpose and that there are no liabilities which extend beyond the description on the face hereof, and the buyer hereby waives all remedies or liabilities, expressed or implied arising by law or otherwise, (including without obligations of the seller with respect to fitness, merchantability and consequential damages) or whether or not occasioned by the seller's negligence.

The seller disclaims any warranty and expressly disclaims any liability for personal injury or damages. The buyer acknowledges and agrees that the disclaimer of any liability for personal injury is a material term for this agreement and the buyer agrees to indemnify the seller and to hold the seller harmless from any claim related to the item of the equipment purchased. Under no circumstances will the seller be liable for any damages or expenses by reason of use or sales of any such equipment.

The seller assumes no liability regarding the improper installation or misapplication of its products. It is the installer's responsibility to check for proper installation and if in doubt the manufacturer is to be contacted.

LIMITED LIFETIME WARRANTY

STATEMENT POLICY

- The warranty policy is the best warranty within the high performance diesel industry.
- All **TS Performance** products have been inspected, tested and trial in the factory laboratories and on the field.
- Nothing in this Statement of Policy shall alter or enlarge the terms of warranties, obligation or liabilities of these products.
- **TS Performance** is not responsible or liable for any products damaged or destroyed due to improper installation.

TERMS OF WARRANTY

- The defective product must be freight prepaid and returned to **TS Performance** for further investigation, otherwise this warranty shall be deemed null and voided and of no effect.
- This warranty is void on any products that show evidence of misapplication, negligence, and improper installation, and abuse, lack of proper maintenance or alternation from its original design.
- In no event will **TS Performance** be liable for any consequential or incidental damages for breach of any express or implied warranty on the product.
- This warranty is not transferable or assignable.
- **TS Performance** is not responsible or liable for any products damaged or destroyed due to improper installation
- **.IN THE EVENT THAT THE BUYER DOES NOT AGREE WITH THIS AGREEMENT: THE BUYER MAY PROMPTLY RETURN THIS PRODUCT IN A NEW ANDN UNUSED CONDITION WITH A DATED PROOF OF PURCHASE TO THE PLACE OF PURCHASE WITHIN TEN (10) DAYS FROM DATE OF PURCHASE FOR A FULL REFUND.**

Continued

TS PERFORMANCE
Products and Other Info found on the
WWW.TSPERFORMANCE.COM

FOR TECHNICAL SUPPORT
(270) 746-9999



WE ARE DIESEL