



KIT CONTENTS:

- iPad Dash Bezel
- Lightning Charging Cable
- Suede Protective Backing

TOOLS NEEDED:

- 7mm Socket
- T10 Torx Bit
- Dremel or Cutting Device
- 2 Part Epoxy or JB Weld

INSTALLATION INSTRUCTIONS

Using a flat head screw driver or plastic Panel popper remove pocket on top of dash. Take your 7mm socket and remove the 2 bolts circled in first picture.



2. Once 7mm bolts are removed pull the dash bezel towards you and it will come loose. Unplug the necessary connections so the bezel can be removed from the truck.



3. Remove the top 2 or 3 buttons from your stock bezel depending which model you have. Remove the 5 orange tabs marked in red in the picture below. Take your T10 bit and remove all screws from the dash bezel.



4. Remove back cover, circuit boards, bottom controls and take your top buttons and 6 of the shorter T10 Screws and put them aside as all of these things will be mounted to your new iPad dash bezel.



5. Using a dremel or cutting device, take your back panel and trim the 3 sides where the yellow tape is marked. Left side is back piece cut. Right side is back piece not cut.



6. Now you will grab your new iPad in Dash Bezel and start re assembling it by taking your top buttons and putting those in the correct slot. Place your bottom buttons in the factory location and then your circuit board back on top making sure it is all aligned in its place. Then take your trimmed back panel and set that on top making sure the A/C plugs come through the holes of the back panel. Take your 5 orange clips and snap them onto the new bezel. Taking your 6 T10 Torx screws put them in the locations circled in the picture below. DO NOT overtighten the torx screws.



7. Next you're going to install your peel and stick suede backing inside the dash bezel to protect your iPad when it is removed. Then insert your iPad in the dash Bezel.



8. Flip Your Dash Bezel over with the iPad in place and insert your lighting cable. Using a 2 part epoxy or JB quick weld you're going to secure your charge cable to your bezel. During this process keep the iPad in the bezel so the charge cable is aligned perfect. Be careful not to let the epoxy run through onto your iPad. Let epoxy fully cure before you remove your iPad. Once cured you're ready to install your dash bezel into your truck.



9. Now that you are back in the truck. Take your lighting charge cable and route it behind the dash to the USB ports in the compartment in front of cup holders. You will need to remove the USB ports and using your dremel make a small round notch like shown in the picture. Route your charge cable out of the notch and plug it into one of the USB ports. Re install USB ports.



10. Plug all Factory plugs back into your dash bezel and install back on the dash. Install the (2) 7mm bolts up top and clip in the top pocket. Now you have completed your Retro Customz iPad In Dash install. Enjoy!

