




Installation Steps:

- ! **If installing in a Model Year 2025+ refer to page 2 before proceeding with installation**

- 1) Move the rear seats forward to fully open the cargo door.
- 2) Remove any contents from the rear cargo area.
- 3) Slide the safe down hinge side first into the rear cargo area. **A1**
- 4) Push the safe downward forcefully to fully seat. **A2**
- 5) Ensure all safe corners are below the top surface of the cargo area. **A3**
- 6) Notice six threaded fittings, two in the front, two in the back, and one on each side.
- 7) Hand thread the six self-drilling screws into each fitting. **A4**
- 8) Tighten each of the self-drilling screws, **DO NOT OVER TIGHTEN**, these screws are designed to cut into the storage bin while turning. Once the screw is fully seated, **STOP**. Over tightening will damage the fitting. **A5**
- 9) Ensure that these instructions are given to the vehicle end-user.
- 10) The installation is now complete.





Installation Steps:

! If installing in a Model Year 2025+ follow these instructions before installation

- 1) If your Bronco is model year 2025 or greater it may have a piece of foam on the bottom of the compartment door (boxed in red). This foam piece must be removed to allow for proper installation of this safe. **A6**
- 2) Starting at any corner, slowly peel the foam away from the door and discard. If you cannot remove the foam, please contact Console Vault customer service. **A7**
- 3) Proceed with the installation as normal starting with step 1 on the previous page.



Combination Lock Reset Guides:

Installation Steps:

IMPORTANT: Make sure to set your combination **BEFORE** installing your safe

Before setting your combination, ensure safe door remains **OPEN** to prevent accidental lockout



⇒ [4 Digit Lock User Guide](#)



⇒ [3 Digit Lock User Guide](#)



⇒ [Elite 4-Digit Lock
User Guide](#)